

Product Specifications



Features

- Operates effectively with a very good read range when attached to Off Metal Surfaces
- Rugged construction for high durability
- Can be attached by screws with the help of two holes
- Flexible Read/Write Range (reader dependent)

Applications

With innovative construction and customized printing compatibility, the Crate Tag is ideal for applications such as:

- Manufacturing
- Logistics
- Plant & Machinery
- Non - Metallic Assets Tracking
- Plastic Trolley/ Pallet Tracking

Physical

Size (L X W X H) in MM	120 x 17 x 3 (Hole Dia: 5, 3)
Size (L X W X H) in Inch	4.7 x 0.6 x 0.1 (Hole Dia: .19, .11)
Operating Temperature	-40°C to +85°C
Storage Temperature	-40°C to +85°C
IP Rating	IP 67
Weight	5.00 g
Material	ABS
Color	Grey
Attachment	With Foam Adhesive Screw or Revit

UHF Crate Tag

Electrical

Protocol	EPC Class 1 Gen 2
Operating Mode	UHF Passive
Operating Frequency	ETSI: 865-868MHz FCC: 902-928MHz (Available on request)
IC Type	Alien Higgs 3 / Higgs 9
Memory	TID : 96 bits EPC : 96 bits User : 512 bits
Data retention	20 years
Write endurance	100,000 cycles
Read Range*	• Up to 12 Meters from a Fixed Reader • Up to 6 Meter from a Handheld Reader

* Read Range is based on ERP of reader antenna

Customization Options

Encoding	Serialized or Variable
Printing	Barcode, QR Code, Logo Etc.
Laser Engraving	Barcode, QR Code, Logo Etc.
Adhesive	Foam Adhesive
IC	Various Options Available, Depending upon requirement
Versions	1. Free Air

For Queries : sales@rfgenie.in

<https://www.rfgenie.in>